HD28 JSB-502X | M28™ body grip jigsaw

- Milwaukee® high performance motor delivers 2800 spm for fast cutting.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- 2-speed selector switch for ideal speed in different materials.
- Patented FIXTEC system for fast keyless blade change and bevel adjustment with snap-in at 0° and 45°.
- Four-stage adjustment of the pendulum action for increased cutting performance and longer saw blade life.
- Adjustable saw dust blower.
- Exact saw blade guidance with large blade support roller on needle bearings fitted in a very low position.

	HD28 JSB-502X
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	90 min
Max. cutting capacity steel (mm)	10
Max. cutting capacity wood (mm)	135
Mitre capacity (°)	45
No load stroke rate (spm)	2100 / 2800
No. of batteries supplied	2
Pendulum action	Yes
Pendulum settings	4
Sound power level (dB(A))	93.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	82.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	5 saw blades, sliding shoe
Stroke length (mm)	26
Supplied in	HD Box
Vibration cutting metal (m/s²)	6.4
Vibration cutting metal uncertainty (m/s²)	1.5
Vibration cutting wood (m/s²)	6.3
Vibration cutting wood uncertainty (m/s²)	1.5
Voltage (V)	28
Weight with battery pack (kg)	3.5