M12 UHL-0 | M12™ LED underhood light

- TRUEVIEW™ high definition light output delivers consistent beam, optimised colour temperature and true representation of colours and detail.
- Two light output settings with 1350 and 600 Lumens to maximise run time and to optimise lighting output.
- Mounting hooks extend 119 cm - 196 cm (47″ - 77″) covering wide cars and trucks.
- Flexible and versatile light bar to rotate vertically, adjust position and remove from the carrier to suit user needs.
- Rubber gripping surface for maximum hold.
- Milwaukee®'s FINISHGUARD™ hooks provide lasting protection against scratches to a vehicle's finish.
- Stainless hook allows to hang the light bar independently from the carrier.

	M12 UHL-0
Battery compatibility	All Milwaukee® M12™ batteries
Battery pack capacity (Ah)	No batteries supplied
Battery type	Li-ion
Charger supplied	—
IP protection class	IP 54
Max. light output High/Medium/Low/Strobe (Lumens)	1350/ -/ 600/ -
Max. run time with M12 B4 battery (h)	4/ -/ 8/ -
No. of batteries supplied	0
Standard equipment	clamping attachement
Supplied in	No kitbox or bag supplied
System	M12
Voltage (V)	12
Weight with battery pack (kg)	1.1