M18 PAL-0 | M18™ pivoting area light

- TRUEVIEW™ high definition lighting with up to 1500 Lumens and up to 20 hours of run time, allows replacement of 500 W halogen.
- Two powerful magnets, a spring loaded clamp and a folding rotating light head design provide multiple mounting options and illumination possibilities from any angle.
- Most compact M18™ flood light designed for the on-the-go needs of service and maintenance trades.
- IP54 rating, the light is protected from dust and splashing water.
- Integrated handle/tie off zone, designed to be carried or tethered while used on a scissor lift.
- Low battery indicator, light flashes when battery pack is low on charge.
- Flexible battery system: works with all Milwaukee® M18™ batteries.

	M18 PAL-0
Battery compatibility	All Milwaukee® M18™ batteries
Battery pack capacity (Ah)	No batteries supplied
Battery type	Li-ion
Charger supplied	–
IP protection class	IP54
Max. light output High/Medium/Low/Strobe (Lumens)	1500 / 600 / 300
Max. run time with M18 B5 battery (h)	4.5 / 10 / 20
No. of batteries supplied	0
Supplied in	No kitbox or bag supplied
System	M18
Voltage (AC) (V)	–
Voltage (DC) (V)	18
Voltage (V)	18
Weight with battery pack (kg)	2.1