K 950 S | 10 kg class drilling and breaking hammer

- 20 J blow energy for hard hitting performance.
- 1700 watt motor - best in class with plenty in reserve for the toughest applications.
- 3 handles - all with AVS (Anti-Vibration-System) and soft grip for comfortable and less tiring use.
- All metal gearcase - optimum seating of the gears for enhanced service life.
- Service indicator light.
- Automatic lubrication system for longer life time.
- In-Line motor design for more comfort in below waist applications.

	K 950 S
Blow energy (EPTA)(J)	20
Full load hammer action (bpm)	975 - 1950
Full load speed (soft hammer) (rpm)	125 - 250
Max. drilling core bit (mm)	150
Max. drilling solid bit (mm)	50
Max. drilling tunnel bit (mm)	80
No load speed (rpm)	125 - 250
Power input (W)	1700
Sound power level (dB(A))	11
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	100
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Additional front spade handle, auxiliary straight handle, dust shield, grease
Supplied in	Kitbox
Vibration chiseling (m/s²)	11
Vibration chiselling uncertainty (m/s²)	2
Vibration drilling (m/s²)	12.5
Vibration drilling into concrete [m|s²]	11
Vibration drilling into concrete uncertainty [m|s²]	2
Weight (kg)	11.8