HD18 H-402C | M18™ 4-mode SDS-plus hammer

- High powered motor gives corded tool performance.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- All metal gear case: optimum seating for gears to enhance service life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Variolock and hammer stop function.
- Mechanical clutch: protects tool when bit binds up.
- Anti-Vibration-System: delivers max. comfort by minimising vibration.

	HD18 H-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Blow energy (EPTA)(J)	2.4
Charger supplied	80 min
Max. drilling concrete (mm)	24
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. drilling wood/ steel/ concrete (mm)	30/ 13/ 24
Max. percussion rate (bpm)	4200
No load speed (rpm)	1400
No. of batteries supplied	2
Sound power level (dB(A))	99
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	88
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle with metal depth gauge
Supplied in	Kitbox
Vibration chiseling (m/s²)	7.4
Vibration chiselling uncertainty (m/s²)	1.5
Vibration drilling (m/s²)	12.2
Vibration drilling into concrete [m|s²]	12.2
Vibration drilling into concrete uncertainty [m|s²]	1.5
Voltage (V)	18
Weight with battery pack (kg)	3.5