PLH 20 | 20 mm SDS-plus 2-mode L-shaped fixing hammer

- Best power to weight ratio in its class - 2.0 J and 1.9 kg.
- 620 watt motor combined with optimised drilling speed results in unsurpassed drilling performance.
- AVS (Anti-Vibration-System) for more comfortable use and less strain on the user.
- Optimised hammer drilling 5 – 12 mm.
- Safety clutch protects user and machine if drill bit jams.
- Forward and reverse mechanism.
- Soft grip handle for comfort.

	PLH 20
Blow energy (EPTA)(J)	2.0
Full load hammer action (bpm)	0 - 4400
Full load speed (soft hammer) (rpm)	0 - 2700
Max. drilling concrete (mm)	20
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. drilling wood/ steel/ concrete (mm)	30/ 13/ 20
No load speed (rpm)	0 - 3700
Power input (W)	620
Sound power level (dB(A))	101
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	90
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Additional handle, depth gauge
Supplied in	Kitbox
Vibration drilling (m/s²)	10.2
Vibration drilling into concrete [m|s²]	12
Vibration drilling into concrete uncertainty [m|s²]	1.5
Weight (kg)	1.9