PLH 32 XE | 32 mm SDS-plus 3-mode L-shaped hammer

- Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 3.8 joule single blow energy.
- 900 watt motor combined with optimised drilling speed results in unsurpassed drilling performance.
- Good balance and easy handling from the compact L-shape design with AVS (Anti-Vibration-System) and soft grip handle.
- Fast tool changing from the FIXTEC system with keyless chuck.
- Heavy Duty magnesium gear casing for optimum seating of gears for a longer operational life.
- Reliable safety clutch protects machine and user.
- Roto-stop and variolock for maximum control when doing light chiselling work.

	PLH 32 XE
Blow energy (EPTA)(J)	3.8
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 800
Max. drilling concrete (mm)	32
Max. drilling masonry (mm)	32
Max. drilling steel (mm)	16
Max. drilling wood (mm)	40
Max. drilling wood/ steel/ concrete (mm)	40/ 16/ 32
Power input (W)	900
Sound power level (dB(A))	106
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	95
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Front handle with metal depth gauge, adaptor with 13 mm keyless chuck, drill bit lubricant
Supplied in	Kitbox
Vibration chiseling (m/s²)	20
Vibration chiselling uncertainty (m/s²)	1.5
Vibration drilling (m/s²)	22
Vibration drilling into concrete [m|s²]	25
Vibration drilling into concrete uncertainty [m|s²]	2.3
Weight (kg)	3.6