PFH 26 | 26 mm SDS-plus 2-mode fixing hammer

- Most compact, slimline fixing hammer available in its class.
- Unmatched performance with 2.4 J blow energy and 4500 bpm.
- Extreme Milwaukee® durability thanks to Integrated metal block technology.
- Innovative and patented internal weight reduction technology.
- Hammer stop function - turns off the hammering action - for screw driving applications or drilling without percussion in wood/metal.
- Brush rotation ring (for same power in forward & reverse action).
- 4 m cable.

	PFH 26
Blow energy (EPTA)(J)	2.4
Full load hammer action (bpm)	0 - 4500
Full load speed (rpm)	0 - 1250
Max. drilling concrete (mm)	26
Max. drilling steel (mm)	13
Max. drilling wood (mm)	30
Max. drilling wood/ steel/ concrete (mm)	30/ 13/ 26
Power input (W)	725
Sound power level (dB(A))	103
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	92
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle with metal depth gauge
Supplied in	Kitbox
Vibration chiseling (m/s²)	8.5
Vibration drilling (m/s²)	13.5
Vibration drilling into concrete [m|s²]	13.5
Vibration drilling into concrete uncertainty [m|s²]	1.5
Weight (kg)	2.4