PLH 28 E | 28 mm SDS-plus 3-mode L-shaped hammer

- Hardest hitting corded SDS hammer in its class. Tough, durable hammer with excellent drilling performance in concrete from the high torque motor and gears and a 4.1 joule single blow energy.
- 800 watt motor combined with optimised drilling speed results in unsurpassed drilling performance.
- Good balance and easy handling from the compact L-shape design with dual patented AVS (Anti-Vibration-System) and soft grip handle.
- Reliable safety clutch protects machine and user.
- Roto-stop and variolock for maximum control when doing light chiselling work.
- XE version comes with fast changing FIXTEC adaptor and 13 mm keyed chuck.
- 4 m durable rubber cable.

	PLH 28 E
Blow energy (EPTA)(J)	4.1
Full load hammer action (bpm)	0 - 4000
Full load speed (rpm)	0 - 1000
Max. drilling concrete (mm)	28
Max. drilling steel (mm)	13
Max. drilling wood (mm)	40
Max. drilling wood/ steel/ concrete (mm)	40/ 13/ 28
No load speed (rpm)	0 - 1500
Power input (W)	800
Sound power level (dB(A))	101.8
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	90.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle, 4m cable, depth gauge, grease
Supplied in	Kitbox
Vibration chiseling (m/s²)	6.8
Vibration chiselling uncertainty (m/s²)	1.5
Vibration drilling (m/s²)	10.6
Vibration drilling into concrete uncertainty [m|s²]	1.5
Weight (kg)	3.4