HD18 PD-0 | M18™ percussion drill

- With its Milwaukee® 4-pole frameless motor it delivers 85 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Heavy Duty 13 mm full metal chuck delivers optimum bit retention.
- Hammer mechanism delivers 28,000 bpm for highly effective masonry drilling.
- 24 stage torque adjustment delivers optimum control for the user.
- 3 stage mode selector allows the user to switch between rotary, screw drive and percussion modes quickly and easily.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

	HD18 PD-0
Battery pack capacity (Ah)	No batteries supplied
Battery type	Li-ion
Charger supplied	—
Chuck capacity (mm)	13
Max. drilling masonry (mm)	16
Max. drilling steel (mm)	13
Max. drilling wood (mm)	55
Max. drilling wood/ steel/ masonry (mm)	55/ 13/ 16
Max. percussion rate (bpm)	28,000
Max. torque (Nm)	85
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1800
No. of batteries supplied	0
Sound power level (dB(A))	97.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	86.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle, belt clip
Supplied in	No kitbox or bag supplied
Vibration drilling into concrete [m|s²]	11.6
Vibration drilling into concrete uncertainty [m|s²]	1.5
Vibration drilling into Metal [m|s²]	<2.5
Vibration drilling into metal uncertainty [m|s²]	1.5
Vibration screw driving (m/s²)	<2.5