M12 BPD-402C | M12™ sub compact percussion drill

- Milwaukee® high performance sub compact percussion drill measures 190 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Optimised handle for better control and improved grip.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light - added user convenience and illumination in low lit working conditions.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all Milwaukee® M12™ batteries.

	M12 BPD-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Charger supplied	80 min
Chuck capacity (mm)	10
Max. drilling masonry (mm)	10
Max. drilling steel (mm)	10
Max. drilling wood (mm)	22
Max. drilling wood/ steel/ masonry (mm)	22/ 10/ 10
Max. percussion rate (bpm)	22,500
Max. torque (Nm)	38
No load speed gear 1 (rpm)	0 - 400
No load speed gear 2 (rpm)	0 - 1500
No. of batteries supplied	2
Sound power level (dB(A))	97
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	85
Sound pressure level uncertainty (dB(A))	3
Supplied in	Kitbox
Vibration drilling into concrete [m|s²]	7.9
Vibration drilling into concrete uncertainty [m|s²]	1.5
Vibration drilling into Metal [m|s²]	1.5
Vibration drilling into metal uncertainty [m|s²]	1.5
Vibration screw driving (m/s²)	0.4
Vibration screw driving uncertainty (m/s²)	1.5