HD28 PD-502X | M28™ percussion drill

- With its Milwaukee® high powered motor it delivers a staggering 90 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Compact size of only 237 mm overall length.
- 13 mm Röhm chuck provides maximum durability.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Built in LED light illuminates the work surface.

	HD28 PD-502X
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	90 min
Chuck capacity (mm)	13
Max. drilling concrete (mm)	20
Max. drilling steel (mm)	16
Max. drilling wood (mm)	65
Max. drilling wood/ steel/ concrete (mm)	65/ 16/ 20
Max. torque (Nm)	90
No load speed gear 1 (rpm)	0 - 450
No load speed gear 2 (rpm)	0 - 1800
No. of batteries supplied	2
Sound power level (dB(A))	97.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	86.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Side handle
Supplied in	HD Box
Vibration drilling into concrete [m|s²]	11.6
Vibration drilling into concrete uncertainty [m|s²]	1.5
Vibration drilling into Metal [m|s²]	<2.5
Vibration drilling into metal uncertainty [m|s²]	1.5
Vibration screw driving (m/s²)	<2.5
Vibration screw driving uncertainty (m/s²)	1.5