M18 ONESLDP-0 | M18™ ONE-KEY™ LED compact site light charger

- Optimise brightness and run time by adjusting the light output from 0 - 9000 Lumens.
- ONE-KEY™ tool customisation allows user to control brightness and set light settings remotely.
- Program automatic schedules to decide during which days/times the light is running.
- Integrated M18™ charger - charges up to 2 batteries sequentially.
- Dual power source, powered by either M18™ REDLITHIUM-ION™ battery packs or use of 2.5 m hardwired cord.
- AC outlet gives the possibility to string multiple lights together.
- Highly durable and impact resistant polycarbonate lens to protect the light from rough jobsite conditions.

	M18 ONESLDP-0
Battery compatibility	All Milwaukee® M18™ batteries
Battery pack capacity (Ah)	No batteries supplied
Battery type	Li-ion
Carry handle	
Charge Type	Sequential
Charger supplied	—
Charging ports	2 x M18™
IP protection class	IP54
Max. light output High/Medium/Low/Strobe (Lumens)	9000/ 4800/ 2500/ -
Max. run time with M18 B9 battery (h)	3.5/ 7/ 14/ -
No. of batteries supplied	0
Power source	AC
Supplied in	No kitbox or bag supplied
System	M18
Voltage (AC) (V)	100 - 240
Voltage (DC) (V)	18
Weight with battery pack (kg)	12.1