M18 BRAID-0 | M18™ right angle impact driver

- Compact right angle impact driver measures 307 mm in length making it ideal for working within confined spaces.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Compact 53 mm head design.
- Multi-handle design for multiple hand positions and maximum comfort.
- ¼″ Hex chuck for quick easy one handed bit change.
- 2 speed settings for wider range of applications.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

	M18 BRAID-0
Battery pack capacity (Ah)	No batteries supplied
Battery type	Li-ion
Charger supplied	—
Impact rate (ipm)	0 - 2400 / 0 - 3400
Max. torque (Nm)	41 / 81
No load speed (rpm)	0 - 1500 / 0 - 2250
No. of batteries supplied	0
Sound power level measured (dB(A))	101,6
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	90,6
Sound pressure level uncertainty (dB(A))	3
Supplied in	No kitbox or bag supplied
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m|s²]	14,8
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m|s²]	1,5
Voltage (V)	18
Weight with battery pack (kg)	1.8