M18 BID-402C | M18™ compact ¼ Hex impact driver

- Compact impact driver measures 140 mm in length making it ideal for working within confined spaces.
- Milwaukee® high performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- Heavy duty full metal gearbox and gears for superior durability and maximum torque.
- ¼″ Hex drive with click lock for single hand loading of bit.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.

	M18 BID-402C
Battery pack capacity (Ah)	4.0
Battery type	Li-ion
Charger supplied	80 min
Impact rate (ipm)	0 - 2450/0 - 3450
Max. torque (Nm)	180
No load speed (rpm)	0 - 2000/0 - 2750
No. of batteries supplied	2
Sound power level (dB(A))	104.8
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	93.8
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Belt hook
Supplied in	Kitbox
Vibration screw driving (m/s²)	12.3
Vibration screw driving uncertainty (m/s²)	2.77
Voltage (V)	18
Weight with battery pack (kg)	1.7