M18 BMS20-0 | M18™ metal shear

- Accurate cuts with maximum cutting depth of 2.0 mm in steel.
- Unique 360° tool-free rotating head with 12 locking positions to access tight spaces and increasing user comfort.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- In-Line wrist design for increased control during cutting.
- Variable speed trigger for extra control during cutting.
- Belt clip for secure mobility.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.

	M18 BMS20-0
Battery pack capacity (Ah)	No batteries supplied
Battery type	Li-ion
Charger supplied	—
Max. cutting capacity aluminium (mm)	3.2
Max. cutting capacity steel (mm)	2.0
Minimum cutting radius (mm)	180
No load speed (rpm)	0 - 2500
No. of batteries supplied	0
Sound power level measured (dB(A))	89,2
Sound power level measured uncertainty (dB(A))	3,0
Sound pressure level (dB(A))	78,2
Sound pressure level uncertainty (dB(A))	3,0
Supplied in	No kitbox or bag supplied
Vibration cutting of sheet meta uncertaintyl [m|s²]	1,5
Vibration cutting of sheet metal [m|s²]	7,07
Voltage (V)	18
Weight with battery pack (kg)	2.6