MS 304 DB | 12 (305 mm) dual bevel sliding mitre saw

- 1800 Watt direct drive motor ensures a quick, clean cut even in hardwood materials.
- Dual integral jobsite lights illuminate the cut line.
- Unique inline motor design - for excellent visibility from both sides to the work piece and better balanced transport.
- Mitre capacity 55° to the left and 60° to the right – for maximum versatility. Mitre detents L & R at: 0°, 15°, 22.5°, 31.6°, 45°, 60°.
- Dual-bevel design – to incline the saw head left and right 0° – 48° with bevel detents L & R at: 0°, 22.5°, 33,85°, 45°, 48°.
- Fast and accurate bevel adjustment.
- Supplied with Work piece clamp, saw blade (60 teeth), vacuum adaptor ø35 / 58 mm, wrench and 3 m cable.

	MS 304 DB
Bevel capacity left (°)	48
Bevel capacity right (°)	48
Blade diameter (mm)	305
Cable length (m)	3
Max. cutting capacity 45° mitre/ 45° bevel (mm)	241 x 57
Max. cutting capacity 45° mitre/ 90° bevel (mm)	241 x 102
Max. cutting capacity 90° mitre/ 45° bevel (mm)	342 x 57
Max. cutting capacity 90° mitre/ 90° bevel (mm)	342 x 102
Mitre capacity left (°)	55
Mitre capacity right (°)	60
No load speed (rpm)	3900
Power input (W)	1800
Sound power level (dB(A))	108
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	95
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Work piece clamp, saw blade (60 teeth), vacuum adaptor ø35 / 58 mm, wrench, 3 m cable
Supplied in	No kitbox or bag supplied
Vibration cutting (m/s²)	<2.5
Vibration cutting uncertainty (m/s²)	1.5
Weight (kg)	29.5