M18 ONEFHIWF34-502X | M18 FUEL™ ONE-KEY™ ¾ high torque impact wrench with friction ring

- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1627 Nm of fastening torque in a compact size of 213 mm, which gives more access in tight spaces.
- The 4 -Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility.
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting.
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- ¾″ friction ring reception.
- Flexible battery system: works with all Milwaukee® M18™ batteries.

	M18 ONEFHIWF34-502X
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	59 min
Impact rate (ipm)	0-850/0-1850/0-2400/0-2400
Max. bolt diameter	M33
Max. fastening torque (Nm)	1627
No load speed (rpm)	0-800/0-1300/0-1800/0-1800
No. of batteries supplied	2
Nut-busting torque (Nm)	0-702/0-1138/0-1627/0-2034
Supplied in	HD Box
Voltage (V)	18
Weight with battery pack (kg)	3.5