M18 FHIWF12-502X | M18 FUEL™ ½ high torque impact wrench with friction ring

- The M18 FUEL™ high torque impact wrench delivers 1356 Nm fastening torque in a compact size of 213 mm, which gives more access in tight spaces.
- 4-Mode DRIVE CONTROL™ allows the user to shift into four different speed and torque settings to maximise application versatility.
- ½″ friction ring reception.
- New LED light is 40 percent brighter than previous model.
- The Milwaukee® POWERSTATE™ brushless motor provides increased efficiency, lasts longer and delivers maximum power.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM-ION™ battery pack provides superior pack construction, electronics, and fade-free performance to deliver more run time and more work over pack life.

	M18 FHIWF12-502X
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	59 min
Impact rate (ipm)	0-950/0-1750/0-2100/0-2100
Max. bolt diameter	M33
Max. fastening torque (Nm)	130/400/1356/1356
No load speed (rpm)	0-550/0-1400/0-1750/0-1750
No. of batteries supplied	2
Nut-busting torque (Nm)	1898
Sound power level measured (dB(A))	103.1
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	92.1
Supplied in	HD Box
Voltage (V)	18
Weight with battery pack (kg)	3.3