M18 ONEIWF12-502X | M18 FUEL™ ONE-KEY™ ½ impact wrench with friction ring

- M18 FIWF12 but with ONE-KEY™ technology.
- Connect via Bluetooth® with the Milwaukee® ONE-KEY™ app.
- Control speed, torque, start - end speeds and LED light.
- Configure to any application choosing optimum tool settings for repeatable precision.
- Program / save profiles for unmatched control.
- Select from a range of application profiles or quickly create your own for perfect results on every trigger pull.
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite.

	M18 ONEIWF12-502X
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Charger supplied	59 min
Impact rate (ipm)	1300/2100/2550/3200
Max. fastening torque (Nm)	300
Max. torque (Nm)	40/120/220/300
No load speed (rpm)	900/1400/1900/2500
No. of batteries supplied	2
Sound power level measured (dB(A))	104.5
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	93.5
Sound pressure level uncertainty (dB(A))	3
Standard equipment	Belt Clip
Supplied in	HD Box
Vibration Impact tightening of fasteners of the maximum capacity of the tool [m|s²]	7.7
Vibration Impact tightening of fasteners of the maximum capacity of the tool uncertainty [m|s²]	1.5
Voltage (V)	18
Weight with battery pack (kg)	1.8