AGS 15-125 C | 1500 W grinder/sander

- Powerful, 1500 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Aligned to the optimum speed for flap grinding discs.
- Soft start for smooth start up.
- Line lock out function to prevent automatic start up after power breakdown.
- Motor overload protection.
- Burst resistant and tool-free quick release safety guard for fast adjustment.
- Filter metal mesh.

	AGS 15-125 C
Brake	No
Disc diameter (mm)	125
Line lock out function	Yes
No load speed (rpm)	7600
Power input (W)	1500
Sound power level (dB(A))	97
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	86
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, side handle, flange, flange nut, spanner, 4 m cable, filter grill
Supplied in	No kitbox or bag supplied
Switch type	Slide lock-on switch
Vibration grinding (m/s²)	5.6
Vibration grinding uncertainty (m/s²)	1.5
Vibration sanding (m/s²)	2.8
Vibration sanding uncertainty (m/s²)	1.5
Weight (kg)	2.4