HD28 AG115-502X | M28™ 115 mm angle grinder

- Milwaukee®'s high performance motor delivers maximum power whilst (optimising) maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Reduced height of gear box and slim girth design deliver optimum ergonomics.
- Fast and easy wheel change with patented FIXTEC nut.
- Burst resistant and tool-free safety guard for best user protection and fast adjustment.
- AVS side handle for most compatible work and less strain to the user.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

	HD28 AG115-502X
Battery pack capacity (Ah)	5.0
Battery type	Li-ion
Brake	No
Charger supplied	90 min
Disc diameter (mm)	115
Line lock out function	Yes
Max. cutting depth (mm)	28
No load speed (rpm)	9000
No. of batteries supplied	2
Sound power level (dB(A))	90
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	79
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Safety guard, additional AVS handle, FIXTEC flange nut
Supplied in	HD Box
Switch type	Trigger lock-on switch
Vibration grinding (m/s²)	5.5
Vibration grinding uncertainty (m/s²)	1.5
Vibration sanding (m/s²)	2.5
Vibration sanding uncertainty (m/s²)	1.5
Voltage (V)	28
Weight with battery pack (kg)	2.8