AGVM 26-230 GEX DMS | 2600 W angle grinder with AVS and kickback protection

- Milwaukee® B-Guard protects both operator and machine from “kickback effect”.
- Powerful, 2600 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- AVS equipped motor housing and additional AVS side handle for more comfortable handling and less strain of body joints.
- Lowest vibration in it's class with only 2.5 m/s².
- 7 position rotatable main handle.
- FIXTEC flange nut for fast and easy change of discs.
- Burst resistant quick release safety guard for easy adjustment.

	AGVM 26-230 GEX DMS
Anti-kickback protection	Yes
AVS Anti-Vibration System	Yes
Brake	No
Disc diameter (mm)	230
Line lock out function	No
Max. cutting depth (mm)	68
No load speed (rpm)	6600
Power input (W)	2600
Rotatable main handle	Yes
Sound power level (dB(A))	104
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	93
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, AVS side handle, Autobalancer, FIXTEC flange nut, 4 m cable
Supplied in	No kitbox or bag supplied
Switch type	Deadman switch
Variable speed	No
Vibration grinding (m/s²)	2.5
Vibration grinding uncertainty (m/s²)	1.5
Vibration sanding (m/s²)	<2.5
Vibration sanding uncertainty (m/s²)	1.5
Weight (kg)	5.8