HD28 CS-32C | M28™ 54 mm circular saw

- Milwaukee® powerful 4200 rpm motor easily cuts most timber construction materials.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Heavy Duty construction with all metal lower / upper blade guards and aluminium shoe.
- Left-blade design for optimal cut-line visibility and control.
- Electronic motor brake, saw blade stops within seconds.
- Ergonomic soft grip handle design for more comfortable use.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.

	HD28 CS-32C
Arbor size (mm)	15.87
Battery pack capacity (Ah)	3.0
Battery type	Li-ion
Blade diameter (mm)	165
Charger supplied	60 min
Max. cutting depth 45° (mm)	39
Max.cutting depth 90° (mm)	54
No load speed (rpm)	4200
No. of batteries supplied	2
Sound power level (dB(A))	102
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	91
Sound pressure level uncertainty (dB(A))	3
Standard equipment	24 tooth blade, rip fence
Supplied in	Kitbox
Vibration level (m/s²)	<2.5
Vibration uncertainty (m/s²)	1.5
Voltage (V)	28
Weight with battery pack (kg)	3.6