# AG 16-125 INOX | 1520 W low speed grinder

- Powerful, 1520 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Digital tacho-electronic with variable speed electronic, soft start, thermal overload protection and no-load speed limitation.
- FIXTEC for tool-free disc change.
- Burst resistant quick release safety guard for easy adjustment.
- Ideal for metal application.
- 4 m rubber cable.
- Ideal speed (7600 rpm) for flap grinding discs.

| | AG 16-125 INOX |
|---|---|
| Max. cutting depth (mm) | 33 |
| No load speed (rpm) | 2000 - 7600 |
| Power input (W) | 1520 |
| Power output (W) | 910 |
| Sound power level (dB(A)) | 100 |
| Sound power level uncertainty (dB(A)) | 3 |
| Sound pressure level (dB(A)) | 89.5 |
| Sound pressure level uncertainty (dB(A)) | 3 |
| Spindle size | M 14 |
| Standard equipment | Quick release safety guard, side handle, FIXTEC flange nut, flange, 4 m cable |
| Supplied in | No kitbox or bag supplied |
| Variable speed | Yes |
| Vibration grinding (m/s²) | 6.8 |
| Vibration grinding uncertainty (m/s²) | 1.5 |
| Vibration sanding (m/s²) | 5.4 |
| Vibration sanding uncertainty (m/s²) | 1.5 |
| Weight (kg) | 2.5 |