AG 16-125 XC/DMS | 1520 W angle grinder

- Powerful, 1520 W "PROTECTOR-MOTOR" with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Digital tacho-electronic with constant speed under load, soft start, thermal overload protection and no-load speed limitation.
- Burst resistant quick release safety guard for easy adjustment.
- 4 m rubber cable.
- FIXTEC for tool-free disc change.

	AG 16-125 XC/DMS
Disc diameter (mm)	125
Max. cutting depth (mm)	33
No load speed (rpm)	11,000
Power input (W)	1520
Power output (W)	910
Sound power level (dB(A))	100.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	89.5
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, side handle, FIXTEC flange nut, flange, flap disc, 4 m cable
Supplied in	No kitbox or bag supplied
Variable speed	No
Vibration grinding (m/s²)	11.1
Vibration grinding uncertainty (m/s²)	1.5
Vibration sanding (m/s²)	3.2
Vibration sanding uncertainty (m/s²)	1.5
Weight (kg)	2.5