AGV 15-125 XC | 1550 W angle grinder with AVS

- Powerful, 1550 W “PROTECTOR-MOTOR” with epoxy resin coated field and Heavy Duty winding protection for increased life time of tool.
- Very compact and slim design for comfortable handling.
- Line lock out function to prevent automatic start up after power breakdown.
- Overload protection to prevent overheating.
- Safety clutch to protect the user from kickback injuries.
- New integrated and innovative FIXTEC tool-free disc change system.
- Burst resistant and tool-free quick release safety guard for fast adjustment.

	AGV 15-125 XC
Anti-kickback protection	Yes
AVS Anti-Vibration System	Yes
Brake	No
Disc diameter (mm)	125
Line lock out function	Yes
Max. cutting depth (mm)	33
No load speed (rpm)	11,000
Power input (W)	1550
Sound power level (dB(A))	97.5
Sound power level uncertainty (dB(A))	3
Sound pressure level (dB(A))	86.6
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, AVS side handle, flange, flange nut, 4 m cable
Supplied in	No kitbox or bag supplied
Switch type	Slide lock-on switch
Variable speed	No
Vibration grinding (m/s²)	4.7
Vibration grinding uncertainty (m/s²)	1.5
Vibration sanding (m/s²)	4.5
Vibration sanding uncertainty (m/s²)	1.5
Weight (kg)	2.6