M18 CAG125XPDB-902X | M18 FUEL™ 125 mm braking grinder with paddle switch

- Milwaukee® designed and built brushless POWERSTATE™ motor with the power to grind and up to 10x more tool life.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection.
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up.
- Premium gearing system - same system as used at high performance corded grinders.
- Slim handle design with paddle switch.
- Removable dust screen to prevent debris entrance, prolonging motor life.

	M18 CAG125XPDB-902X
Battery pack capacity (Ah)	9.0
Battery type	Li-ion
Brake	Yes
Braking time (s)	< 2
Charger supplied	95 min
Disc diameter (mm)	125
Line lock out function	Yes
Max. cutting depth (mm)	33
No load speed (rpm)	8500
No. of batteries supplied	2
Sound power level measured (dB(A))	89.9
Sound power level measured uncertainty (dB(A))	3
Sound pressure level (dB(A))	78.9
Sound pressure level uncertainty (dB(A))	3
Spindle size	M 14
Standard equipment	Quick release safety guard, AVS side handle, flange,Fixtec nut, 2x dust screens
Supplied in	HD Box
Switch type	Paddle (Deadman) switch
Vibration grinding (m/s²)	4.61
Vibration grinding uncertainty (m/s²)	1.5
Vibration sanding (m/s²)	2.15
Vibration sanding uncertainty (m/s²)	1.5
Voltage (V)	18
Weight with battery pack (kg)	3.0