

**G** **HSS-E** **DIN 5156**

**Filettatura gas cilindrica**  
DIN ISO 228



			<b>F 7916</b>		<b>F 7918</b>		<b>F 7919</b>		<b>F 7920</b>	
Modello			7011 Rapid		6002		6030-Rsp		6040 Grulo	
DIN			5156		5156		5156		5156	
Esecuzione/Forma			B/Imbocco corretto		C		C/Elica destra 15°		C/Elica destra 40°	
Acciaio			HSS-E		HSS-E		HSS-E		HSS-E	
Per fori										
<b>Per materiali gruppo:</b>			<b>1.1</b>		<b>1.1</b>		<b>1.1</b>		<b>1.1</b>	
<b>G</b>	Filetti per pollice	Ø preforo mm	<b>Codice</b>	Cad. €	<b>Codice</b>	Cad. €	<b>Codice</b>	Cad. €	<b>Codice</b>	Cad. €
1/8	28	8,80	<b>F 7916 0018</b>		<b>F 7918 0018</b>		<b>F 7919 0018</b>		<b>F 7920 0018</b>	
1/4	19	11,80	<b>F 7916 0014</b>		<b>F 7918 0014</b>		<b>F 7919 0014</b>		<b>F 7920 0014</b>	
3/8	19	15,25	<b>F 7916 0038</b>		<b>F 7918 0038</b>		<b>F 7919 0038</b>		<b>F 7920 0038</b>	
1/2	14	19,00	<b>F 7916 0012</b>		<b>F 7918 0012</b>		<b>F 7919 0012</b>		<b>F 7920 0012</b>	
5/8	14	21,00	<b>F 7916 0058</b>		—	—	<b>F 7919 0058</b>		<b>F 7920 0058</b>	
3/4	14	24,50	<b>F 7916 0034</b>		<b>F 7918 0034</b>		<b>F 7919 0034</b>		<b>F 7920 0034</b>	
7/8	14	28,25	—	—	—	—	<b>F 7919 0078</b>		<b>F 7920 0078</b>	
1	11	30,75	<b>F 7916 0001</b>		<b>F 7918 0001</b>		<b>F 7919 0001</b>		<b>F 7920 0001</b>	
1 1/8	11	35,50	—	—	<b>F 7918 0118</b>		<b>F 7919 0118</b>		—	—
1 3/8	11	41,50	<b>F 7916 0138</b>		<b>F 7918 0138</b>		<b>F 7919 0138</b>		—	—

Tabella per la scelta dei maschi e indicazioni sui rivestimenti, vedere pag. 552÷555